

Spiral Tube Winders LSW - 2A | MW-8 | MW-16 | HSW - 20A

- Wide range of core diameters and thicknesses are available
- Safety features for operator comfort
- Proven mechanical designs for efficient setup, operation, and maintenance
- Simple controls for production made easy
- Additional equipment available:
 - Cascade and immersion tanks
 - Paper creel stands
 - Festoons



Companies worldwide rely on PACO Winders & Elsner Engineering to supply and service their paper tube, can and core converting, winding and cutting requirements.

Find us at: 📞 717-637-5991





 $oxed{oxed}$ eew@elsnereng.com



elsnereng.com



475 Fame Ave, Hanover, PA 17331 USA





Spiral Tube Winders LSW - 2A | MW-8 | MW-16 | HSW - 20A

Spiral Tube Winders	LSW- 2A	MW - 8A	MW - 16	HSW- 20A
Tube Diameter Range	.37" ID to 3" OD	.75" ID to 8" OD	.75" ID to 16" OD	2"ID to 20"OD
Maximum Wall Thickness	.20"	.66"	.66"	1.00"
Maximum Belt Feet/Min *	355	450	450	425

Drives

All machines are available with A.C. vector drives, D.C. drives, hydraulic P\power units, and mechanical drives in various H.P. ratings.

Companies worldwide rely on PACO Winders & Elsner Engineering to supply and service their paper tube, can and core converting, winding and cutting requirements.

Find us at: 1, 717-637-5991







475 Fame Ave, Hanover, PA 17331 USA



elsnereng.com





^{*}Variables: diameter, wall, length