

Air Operated Saw

LS - 3A | MS-8A | CS-16A | CS-20A

- Rugged Construction
- Choice of electrical or mechanical target assemblies
- Easy set up
- Decades of proven reliability



Companies worldwide rely on PACO Winders & Elsner Engineering to supply and service their paper tube, can and core converting, winding and cutting requirements.

Find us at:  717-637-5991

 eeew@elsnereng.com

 elsnereng.com

 475 Fame Ave, Hanover, PA 17331 USA



©Elsner Engineering Works, Inc. 2023

Air Operated Saw

LS - 3A | MS-8A | CS-16A | CS-20A

Air Operated Saw Model	LS-3A	MS-8A	CS-16A	CS-20A	Units
Min Tube ID	0.37	0.50	2.00	2.00	Inches
Max Tube OD	3.0	8.0	16.0	20.0	Inches
Max Wall Thickness	0.20	0.35	0.75	0.88	Inches
Min Cut off Length	8.0	10.0	15.0	15.0	Inches
Tolerance of Cut Off Length	±1/16	±1/16	±1/16	±1/16	Inches
TEFC Motor Size	1	3	7 1/2	10	HP
Max Production Rate*	38 to 42	36 to 44	38 to 40	32 to 36	Cuts/Min

*Variables: diameter, wall, length

Companies worldwide rely on PACO Winders & Elsner Engineering to supply and service their paper tube, can and core converting, winding and cutting requirements.

Find us at:  717-637-5991



 eeew@elsnereng.com

 elsnereng.com

 475 Fame Ave, Hanover, PA 17331 USA



©Elsner Engineering Works, Inc. 2023